

# SPS<sup>™</sup> Removal / Installation Instructions

# Control of the second s

### SPS<sup>™</sup> Assembly Removal Instructions

- 1. Remove the integral gasket<sup>®</sup>.
- Remove the top screws that secure the SPS<sup>™</sup> assembly<sup>®</sup> to the basket<sup>®</sup>. Eight top screws<sup>®</sup> secure the SPS<sup>™</sup> assembly to the top of the frame (mounting flange) and 10 bottom screws<sup>®</sup> (G512) and 8 bottom screws<sup>®</sup> (G510) secure the SPS<sup>™</sup> assembly to the frame (top plate/spider).
- 3. Once all the screws are removed, the SPS<sup>™</sup> assembly will slide out of the basket. Use care when removing the SPS<sup>™</sup> assembly from the basket.

Boston Acoustics, Inc. 300 Jubilee Drive, Peabody, MA 01960 USA T: 978.538.5000 F: 978.538.5100 W: bostonacoustics.com

SPS, is a trademark and Boston, Boston Acoustics, and the Boston Acoustics logo are registered trademarks of Boston Acoustics, Inc. Specifications are subject to change without notice.

042-002216-0

All rights reserved. Covered by patents issued and/or pending.  $\circledast$  2004 Boston Acoustics, Inc.

# G512 Part List:

- 1. Speaker Gasket
- 2. SPS Assembly
- 3. G5 Basket Assembly
- 4. Top Screw x 8
- 5. Bottom Screw x 10

# G510 Part List:

- 1. Speaker Gasket
- 2. SPS Assembly
- 3. G5 Basket Assembly
- 4. Top Screw x 8
- 5. Bottom Screw x 8

### SPS<sup>™</sup> Assembly Installation Instructions

- Install the SPS<sup>™</sup> assembly<sup>®</sup> into the basket<sup>®</sup>. The basket and frame are notched to prevent the SPS<sup>™</sup> assembly from being installed incorrectly. Make sure the SPS<sup>™</sup> assembly mounts firmly into the frame with the speaker terminals located in the correct location.
- Install the top screws that secure the SPS<sup>™</sup> assembly<sup>®</sup> to the basket. Eight top screws<sup>®</sup> secure the SPS<sup>™</sup> assembly to the top of the frame (mounting flange) and 10 bottom screws<sup>®</sup> (G512) and 8 bottom screws<sup>®</sup> (G510) secure the SPS<sup>™</sup> assembly to the frame (top plate/spider).
- *3.* Install the integral gasket<sup>0</sup>.

Warning: If disassembling the G5 for customization; where the SPS<sup>™</sup> will be reused, store the SPS<sup>™</sup> assembly in a safe location with the voice coil facing up and protected; damage to the voice coil, even minor damage, can ruin the SPS<sup>™</sup> assembly.